



MT. ROYALE™

GLAZED PORCELAIN | REVEAL IMAGING®

RAGNO®

ARTFULLY REIMAGINED™





Pecan

MT. ROYALE™

Mt. Royale™ delves into the popular wood-look trend with natural graining imitating the appearance of walnut wood. This large-format style possesses a realistic surface, offering the beauty of a traditional wood-look with lifelike graining and soft undulated grooves for added texture. Broaden your design with five organic colors in Natural, Pecan, Walnut, Gunstock and Gray on a popular 6 x 36 plank.





MT. ROYALE™

GLAZED PORCELAIN | REVEAL IMAGING®


FLOOR TILE



MR01 Natural



MR02 Pecan



MR03 Walnut



MR04 Gunstock




MR05 Gray

USAGE

Floors	Walls	Countertops
F	W	C

SIZES

		THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
 6 x 36 Floor Tile	(5-7/8" x 35-7/16") (15.00 cm x 90.00 cm)	5/16"	13.05	9

APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	●
Wet & Level – Interior Floor	≥ 0.42	●
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	●
Countertops	N/A	●
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit ragnousa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

GROUT JOINT RECOMMENDATION	SHADE VARIATION
3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	V3 High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	FLOOR RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	III

For additional information on test results, visit us at: ragnousa.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards. Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: ragnousa.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to ragnousa.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information visit, ragnousa.com.



Floor Tile



Wall Tile



Reveal Imaging®



Pre-Consumer Recycled Content



All or select items within this series meet the requirements for these qualifications. For more information visit ragnousa.com.

PHOTOGRAPHY INDEX

Cover

Mt. Royale™ in Walnut 9 x 36 on floor
Realstone Quartzite™ in Grigio Random Linear
Mosaic 12 x 24 Sheet on fireplace

Page 2

Mt. Royale™ in Natural 9 x 36 on floor

Page 3

Mt. Royale™ in Pecan 9 x 36 on floor
Aura Dolce™ in Latte, Cinnamon & Blue Ice 6 x 18 on wall

Page 4

Mt. Royale™ in Walnut 9 x 36 on floor
Realstone Quartzite™ in Grigio Random Linear Mosaic
12 x 24 Sheet on backsplash and fireplace

RAGNO®

7834 C.F. Hawn Freeway
Dallas, TX 75217 USA