

Premiere Tile Group

# 7700

New  
Products!

# EASY CLEAN

**Premium "Green"  
Sound & Moisture Control  
MS Polymer Wood  
Flooring Adhesive**

OWNED & OPERATED  
IN USA



Introductory Price  
\$140.00 each 1-35  
buckets  
\$125.00 each 36  
+buckets

## TECHNICAL DATA SHEET

Introductory price ends 03/31/2020

DriTac 7700 Easy Clean is a single-component, premium "green" sound and moisture control MS polymer wood flooring adhesive. Easy Clean is extremely easy to clean off the surface of hardwood flooring wet or dry. This multiple solution product meets and/or exceeds all IIC and STC building code requirements for sound reduction.

### ATTRIBUTES

- Zero Isocyanates
- Low Odor
- Contains No Water
- Nonflammable
- Controls MVER up to 15 lbs./85% RH
- Easy to Clean When Wet or Dry
- One-Day, One-Step System
- Helps Contribute to LEED Credits

### FLOORING TYPES

- Solid Wood Planks
- Bamboo
- Plain-Back Parquet
- Recycled Rubber
- Multi-Ply Engineered Plank
- Acrylic Impregnated Wood
- Exotic Multi-Ply Engineered Plank
- Cork/Rubber/Foam Underlayment

### Sound Control Performance Properties

Method	Subfloor	Flooring	Ceiling	Results	Test
ASTM E 492-09 & E 989-06	8" Concrete	1/2" Engineered Wood	No Suspended Ceiling	54	IIC
ASTM E 492-09 & E 989-06	8" Concrete	1/2" Engineered Wood	Suspended Ceiling	74	IIC
ASTM E 90-4 & ASTM E 413-10	8" Concrete	1/2" Engineered Wood	No Suspended Ceiling	53	STC
ASTM E 90-4 & ASTM E 413-10	8" Concrete	1/2" Engineered Wood	Suspended Ceiling	67	STC

### AVAILABLE CONTAINER SIZE

- 4-Gallon Pail

**Green Label Plus, Indoor Air Quality (IAQ) Certified!**



### 5-IN-1 SYSTEM SOLUTIONS



# DriTac

Adhering to Excellence

Premiere Tile Group

# 8801 CoverGuard

Hard Surface Protective Foam

OWNED AND OPERATED  
IN USA



Introductory price  
\$86.00/roll

## TECHNICAL DATA SHEET

Introductory price ends 03/31/2020

CoverGuard provides scratch and dent protection for newly installed floors and surfaces to prevent damage from occurring during and after the installation process. DriTac 8801 is porous and will allow sub-surface moisture to pass through. CoverGuard resists surface spills and water spots on the top of the film surface.

### FOR USE ON

- Concrete
- Wood
- Tile
- Stone
- Linoleum
- LVT
- WPC
- Most Floor Types New or Existing
- Countertops
- Furniture
- Cabinets

### INSTALLATION INSTRUCTIONS - 4 EASY STEPS

1. Sweep, vacuum, and remove debris from the surface, prior to rolling out CoverGuard.
2. Roll out CoverGuard over the surface. Always install with the scored film layer on top.
3. Use duct tape to secure the flooring sheets together. If using CoverGuard with lip and tape system, connect the extended film lip to the other end of the next roll by peeling off the liner of the adhesive tape and adhering it to the extended film lip.
4. Connect the rolls together evenly to prevent overlapping from occurring and to avoid gapping between the foam.

### Bonus Step

5. CoverGuard is reusable, roll it up and transport it to the next job.

### ATTRIBUTES

- 1.85 mm thickness
- 4' x 150' = 600 sq. ft./roll
- Anti-Crush Mechanical Properties
- **Water & Stain Resistant:** CoverGuard protects from stains, oils and chemicals.
- **Tear Resistant:** CoverGuard has a fused film layer that is puncture resistant.
- **Aerated:** CoverGuard is scored and features a breathable surface to allow free air flow of surface moisture, while preventing topical water and spills from seeping through.
- **Lays Flat:** CoverGuard is a grooved foam which remains flush to the floor and helps prevent the risk of tripping or falling on the floor.

# DriTac

Adhering to Excellence